



SE650

Rugged-Reliable Two-way Radio



*Support LTE(4G)/WCDMA(3G)/GSM(2G)
Network*

- Worldwide Communication Range
- 1.8 Inch Color LCD Display
- Group Call and Individual Call
- Support REAL PTT Platform



SE650

Handheld Two-way Radio

<http://www.sfecom.cn>

Product Features

- 1.8-inch color screen, different backlight modes optional
- Time and Date Calibration
- 2/3/4G network can be manually/automatically switched
- GPS positioning function
- Displaying the user name and group name
- Support group call, individual call
- Signal strength Indicator
- Current Battery Indicator
- Key lock/unlock function
- Support Emergency Alarm(SOS)
- Voice Code 4K/8K optional
- REAL-PTT platform

Specifications

Cat 4 Version Frequency Range	B1/B3/B5/B7/B8/B20@FDD LTE
	B38/B40/B41@TDD LTE
	B1/B5/B5@WCDMA
	B3/B8@GSM
	B1/B2/B3/B4/B5/B7/B8/B28@FDD LTE
	B40@TDD LTE
	B1/B2/B5/B8@WCDMA
	B2/B3/B5/B5@GSM
	B2/B4/B5/B12/B13/B14/B66/B71@FDD LTE
Cat 1 Version Frequency Range	B2/B4/B5@WCDMA
	B1/B3/B5/B7/B8/B20@FDD LTE
Cat 1 Version Frequency Range	B38/B40/B41@TDD LTE
Operating System	LINUX
GPS	Yes
SOS	Yes
Working Mode	Semi-Duplex
RX Sensitivity	LTE ≤-96dBm(4G)
	GSM/WCDMA≤-108dBm (2G/3G) ;
RF Power	23dBm≤P≤30dBm
Audio Output	500mW
Working Voltage	DC3.7V
Battery Capacity	5200mAh
Dimension	52X33X102mm
Weight	Around 220g (Battery& Antenna included)
Working Temperature	-20°C - 60°C
Storage Temperature	-30°C - 80°C

Above specifications are tested according to TIA/EIA-603.

Above specifications are subject to change without any notice due to technology enhancement.

Accessories



SFE Quanzhou SFE Electronic Technology Co.,Ltd
Address: No.35, Yangming Street, Shuangyang, Luojiang District, Quanzhou City,
Fujian Province 362012, P.R. China

SFE retains the right to change the product design and specifications without notices. If any printing mistake occurs, SFE will not bear any relevant responsibility.

© 2024 SFE Electronic Technology Co.,Ltd All Rights Reserved

Your Local Dealer